




NOTES:

1. CONNECTOR - SG3106F-32-17S(476)
2. CABLE - 10 AWG (4) CONDUCTORS, OVERALL BRAIDED SHIELD: CABLE OD = 13.6MM (.535")
3. PROTECTIVE CAP - EP-32 CAPPLUGS
4. BEND RADIUS = 82MM (3.21") MAX

xxx = CABLE LENGTH (METERS)	REF EQUIVALENT MEASURE (FT)
01 = 1 M	01 = 3.28 FT
03 = 3 M	03 = 9.84 FT
05 = 5 M	05 = 16.40 FT
07 = 7 M	07 = 22.97 FT
09 = 9 M	09 = 29.53 FT
11 = 11 M	11 = 36.09 FT
13 = 13 M	13 = 42.65 FT
15 = 15 M	15 = 49.21 FT



REAR FACE OF SOCKET INSERT

REVISIONS			
REV	DESCRIPTION	DATE	APPD
1	RELEASE DRAWING	6/3/04	

TOLERANCES UNLESS SPECIFIED

BORING: = H12 ✓
 SURFACE FINISH: = 63 Ra ✓
 DECIMAL .xxx ±.12 (.005)
 DECIMAL .xx ±.25 (.010)
 DECIMAL .x ±.51 (.020)
 FRACTION ±.40 (.016)
 ANGLE (MM/INCHES) ±.030

REMOVE ALL BURRS/BREAK SHARP EDGES AS SHOWN (0.10°)

CUSTOM MOTORS INC

190MM/10 AWG/32-17S

PROPRIETARY RIGHTS OF CUSTOM MOTORS ARE INCLUDED IN THE INFORMATION DISCLOSED HEREIN. THIS INFORMATION DOES NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.

CUSTOMER: DRAWING: DFLA SHEET: 1 OF 1

SCALE: 1:1 DATE: 6/3/04 DRAWING NO.: CMPxxM-10C REV.: 1