REV DESCRIPTION

1 RELEASE DRAWING 2 CHGS TO PIN/COLOR CHART

12/1/04

10/20/04 DATE

APP'D

REVISIONS

- NOTES:

 1. MILLIMETERS (INCHES)

 2. TURCK EQUIVALENT IS RKM 66-*M/S618/S771/CS...

 3. BEND PADIJUS IS 132-00MM (5.2 INCHES)

 4. "XX" INDICATES LENGTH OF CABLE IN METERS

 5. CABLE LENGTH TOLERANCE +4% (OR 50MM)/-0% (OR 0MM) WHICHEVER IS GREATER


 6. STRIP LENGTH TOLERANCE: ±0.5MM

-40°C TO +105°C (-40°F TO +221°F)	TEMPERATURE RANGE
20 AWG/FOIL SHIELD	DRAIN/SHIELD
6 X 16 AWG	NUMBER OF CONDUCTORS [AWG]
PVC	CONDUCTOR INSULATION MATERIAL
PVC/BLACK	OUTER JACKET MATERIAL/COLOR
600 V	RATED VOLTAGE [V]
9.0 A	RATED CURRENT [A]
BRASS/NICKEL	COUPLING NUT MATERIAL
BRASS/GOLD	CONTACT MATERIAL/PLATING
THERMOPLASTIC PUR	CONTACT CARRIER MATERIAL/COLOR
THERMOPLASTIC PUR/BLACK	MOLDED HEAD MATERIAL/COLOR
SPECIFICATIONS	SPEC

PROTECTION CLASS

MEETS NEMA 1,3,4,6P AND IEC IP67

xx = CABLE LENGTH	REF EQUIVALENT
(METERS)	MEASURE (FT)
01 = 1 M	01 = 3.28 FT
03 = 3 M	03 = 9.84 FT
05 = 5 M	05 = 16.40 FT
07 = 7 M	07 = 22.97 FT
09 = 9 M	09 = 29.53 FT
11 = 11 M	11 = 36.09 FT
13 = 13 M	13 = 42.65 FT
15 = 15 M	15 = 49.21 FT



©RED=1 5=BLU©	Ž.	500		[®] WHT=2 4=ORG [®] L	3=GRN	•	FEMALE PIN-OUT
	6 = BLACK ②	5 = BLUE @	4 = ORANGE @	3 = GREEN @	2 = WHITE @	1 = RED ②	PIN = COLOR
	ΦW	(BRK)	(BRK)	PE GND	ΦV	φU	FUNCTION

SOURCE DRAWING - FOR REFERENCE ONLY

MATERIAL:	FINISH:	REMOVE ALL BURRS. BREAK SHARP EDGES. 25MM (.010") OR 45° CHAMFER	M (INCHES)	DECIMAL XX ± .25 (.010) DECIMAL X ± .61 (.020) EBACTION + .40 (.016)	AL XXX	SURFACE FINISH: = 63 Ra	TOLERANCES UNLESS SPECIFIED
SCALE DATE DRAWING NO. 11.1 10/20/04 CMPBxxM-16K 2	CUSTOMER: DRAWN: DFLA SHEET: 1 OF 1	PROPRIETARY RIGHTS OF CUSTOM MOTORS ARE INCLUDED IN THE INFORMATION DISCLOSED HERRIN, THIS DRAWMIG ADDOR DOCUMENT SHALL NOT BE REPRODUCED OF TRANSFERRED TO OTHER DOCUMENTS OR USED OR DISCLOSED TO OTHER SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR USED OR DISCLOSED TO OTHERS FOR ANY PURPOSE EXCEPT FOR WHICH WAS SPECIFICALLY FURNISHED.	MOLDED CABLE WITH FLYING LEADS	PWR/BRK CABLE 40/60/80MM MTRS		CUSTOM MOTORS INC	-

SUGGESTED VENDOR:

VENDOR NAME: TURCK INC VENDOR P/N: SEE STOCK CODE NO.